

# レーザー加工による表面微細構造の撥水特性付与に関する研究

櫻井俊光<sup>1</sup>、染川智弘<sup>2</sup>、藤田雅之<sup>2</sup>、本山秀明<sup>1,3</sup>

<sup>1</sup> 国立極地研究所

<sup>2</sup> レーザー技術総合研究所

<sup>3</sup> 総合研究大学院大学

## Hydrophobic properties of laser induced periodic surface structures for ice coring drill

Toshimitsu Sakurai<sup>1</sup>, Toshihiro Somekawa<sup>2</sup>, Masayuki Fujita<sup>2</sup>, and Hideaki Motoyama<sup>1,3</sup>

<sup>1</sup>*National Institute of Polar Research,*

<sup>2</sup>*Institute for Laser Technology*

<sup>3</sup>*SOKENDAI (The Graduate University for Advanced Studies)*

We investigated hydrophobic properties of a stainless steel and a high-molecular polyethylene using the laser induced periodic surface structures (LIPSS) method. For the surface processing, we used 800 nm wavelength regenerative amplified 100 femto-second plus laser (Ti: sapphire) operated at a repetition rate of 1kHz. The laser intensity is varied from 80 to 360 mJ/cm<sup>2</sup> and the sweep rate is constant at 20 mm/second. To evaluate the hydrophobicity of the surface, we measured a contact angle of water droplets on the surface. As a result of the measurement, the contact angle increased when the stainless steel and the high-molecular polyethylene surfaces was processed. In other words, hydrophobic properties are provided at the surfaces. The optimum laser intensity depends on the materials, the stainless steel and the high-molecular polyethylene, respectively. The hydrophobic property is useful for avoiding adsorbed ice on the stainless steel and the high-molecular polyethylene which is used for a part of our ice coring drill. We believe that the technology can use for the deep ice coring drill to avoid an adsorption of re-frozen ice and water from a deep part of the Antarctic ice sheet.