

1-year observation of imaging spectrum for aurora and airglow in near infrared wavelength (1.0-1.6 microns) at Syowa Station

Takanori Nishiyama¹, Makoto Taguchi², Hidehiko Suzuki³, and Takeshi Sakanoi⁴

¹*National Institute of Polar Research, Japan*

²*Rikkyo University*

³*Meiji University*

⁴*Grad. School of Science, Tohoku Univ.*

The motivation of this study is further understanding of dayside magnetosphere and terrestrial atmosphere coupling system by using continuous observation. Dayside aurora, polar patch, and airglow should be key phenomena for the understanding. In particular, those phenomena in near infrared (NIR) wavelength are crucially important because lower background sky luminosity by Rayleigh scattering may allow us to conduct ground-based optical observation even in dayside. Continuous dayside optical monitoring with high temporal and spatial resolutions in aurora region and cusp give us a clue to understanding of substorm pre-onset sequences at cusp region, magnetopause dynamics related to solar wind shocks, and wave-particle interactions due to electromagnetic ion cyclotron waves and whistler mode chorus. However, NIR aurora has a total lack of its spectral information with enough resolution to make a feasibility study in comparison to that in visible wavelength.

We designed a narrow field spectrometer with medium-high spectral resolution that mainly consists of Czerny-Turner type imaging spectrometer (HORIBA, iHR320) with one entry port and two exit ports. This spectrometer has two mirrors and three diffractive gratings in a rotating turret. A toroidal mirror for collimating corrects for astigmatism so that the tangential (resolution optimized) and sagittal (imaging optimized) focal planes cross at the center of the focal plane. Another larger focus mirror allows the entire flat field to be used without vignetting. Collecting optics, equipped outside the spectrometer, are a gold coated off-axis parabolic mirror and a NIR longpass filter for removal of secondary diffracted light in visible wavelength. Two detectors for two exit ports are NIR-photomultiplier tube (PMT) module with thermoelectric (TE) cooling system (Hamamatsu, H10330C-75) and InGaAs camera with 640 x 512 pixels and TE cooling in 4 stages (Photon etc., ZephIR 1.7). NIR-PMT module in combination with an exit slit measures precisely individual emission spectrum with high resolution of 0.006 nm. On the other hand, InGaAs camera covers wider spectral ranges (200 nm, 45 nm, 25 nm) and medium spectral resolutions (0.31 nm, 0.070 nm, 0.038 nm) depending on the three gratings (150 gr/mm, 600 gr/mm, 900 gr/mm). The two detectors cannot be operated simultaneously but can be easily switched by a software.

We started ground-based spectroscopic observation in NIR wavelength ranging from 1.0 to 1.6 microns, which covers auroral emissions in N₂ 1st Positive (1.2 microns) and N₂⁺ Meinel (1.1 and 1.5 microns) [Jones 1974; Zhou et al., 2007], at Syowa Station (69.0°S, 39.6°E) in Antarctica from March 2018. In this presentation, we are going to report initial results based on one year observation.

References

Vallance Jones, A., *Aurora*, 301 pp., Springer, New York, 1974.

Zhou, X.-Y., D. Lummerzheim, R. Gladstone, and S. Gunapala, Feasibility of observing dayside aurora using NIR camera onboard high-altitude balloons, *Geophys. Res. Lett.*, 34, L03105, doi:10.1029/2006GL028611, 2007.